



Bumper Specialties, Inc.

GENERAL SPECIFICATION SHEET

Features

- UL Recognized Component
- Easy 'Peel-Off' Application
- Superior Abrasion Resistance
- Crack-Resistant & Resilient
- Non-Staining & Non-Marring
- Vibration & Shock Dampening
- Superb Coefficient of Friction & Resistance to Skidding
- Contains No Plasticizers, Oils or Fillers, commonly used in our competitors' products

Standard Colors: Clear & Black

Our most popular bumpers! Every bumper is available in Clear and Black. The crystal clear bumper is nearly invisible when used for on colored or transparent surfaces .

Additional Colors: White, Brown & Gray

Most bumpers are stocked in every color and ready for shipment. Most colors are inventoried based on popularity. Please call to confirm availability of white, brown and gray. There is no additional charge for clear or pigmented Bumpers.

Custom Shapes & Colors

We are the only company that provides full engineering support to help you design a bumper to meet your particular needs! Our staff will meticulously assist your company with the completion of any project. A one-time charge (this differs with size) for tooling and set-up applies. Your final cost/m (m=thousand) will be consistent with our existing line of bumpers. The volume of polyurethane required for custom shapes, difficulty of manufacturing, and normal and customary waste are factors in pricing. You can be assured we are dedicated to providing you with the most competitive prices in the global marketplace!

Special Die-Cut Pads

Available die-cut in strips or smaller pads for a minimal cost/m and a one-time tool charge.

NEW Soft Durometer for Sound Dampening

Please call for the availability of profiles that are available in SD. (The -SD suffix designates the softer durometer) Not for load bearing applications.

Application Instructions

To obtain a maximum bond, surfaces need to be smooth, non-porous, clean, dry and free of all debris, oils and solvents. Clean the surface with a low strength solvent such as isopropyl alcohol (rubbing alcohol) or heptane. Follow solvent manufacturer's precautionary warnings and suggested handling procedures when using solvents. Bend pad slightly grasping bumper on sides without touching the adhesive. Apply to surface with enough pressure to ensure a complete bond. Allow a dwell time of 24 hours before exposing to heavy force or weight. The composition of this product contains no migratory plasticizers of any kind, which would mar surfaces of contact. Users should evaluate the suitability of our Bumpers for a specific application under actual conditions.

Tolerances

Our products are manufactured within a tolerance of ± 0.020 " (0.5mm).

Ordering

Please indicate: Part Number, Color, Quantity, Type of Adhesive, Special Cutting / Handling / Shipping

Minimum order is one carton.

Orders must be placed in full carton increments.

All domestic sales are subject to our general terms and conditions: 1% 10, net 30 days.

All quotations and prices are FOB West Deptford, New Jersey.

Quantity discounts apply.

Should further assistance be required contact your Bumper Specialties, Inc. representative.